

TIP TIG MANUAL HOT WIRE WELDING SYSTEM

complete with

- 1000010 - HOTWIRE FEEDER
- 10001135 - INTERCONNECTING CABLE 10' (Miller / Lincoln)
- 10002460 - WP18SC Torch
- 77701000-A - WP 18SC Consumables Kit



Technical Specifications

TIP TIG Feeder

Digitally Controller TIP TIG Microprocessor	
Wire feed motor / Oscillation motow PWM controller	
Wire:	.030, .035, .045, .068
Filler material:	All
4-roller feed system:	5.6- 630 ipm (0.15-16m/min)
Frequency of oscillation:	16Hz
Input Voltage:	32 VAC
Duty cycle at 40 Deg C:	500A/100% d.c.
Weight:	39.2lbs (18kg)
Dimensions (HxWxD)	31.1x13x17.2 790x330x445mm

TIP TIG Hotwire Module

TIP TIG Hotwire Power Supply	160AMP 115VAC
TIP TIG Transformer	115/32 VAC 250VA
Fuse:	8A
Main Switch	
Knob POT for Hotwire adjustment	
Switch for On/Off Hotwire Power Supply	
Connection Cables from Hotwire Module to Feeder	4' (1.2m)
Connection Cables from TIP TIG to Power Supply	10' (3.04m)
Input Voltage:	115 VAC
Duty cycle at 40 Deg C:	110A/100% d.c.
Weight:	52lbs (24kg)
Dimensions (HxWxD)	31.1x13x21.4 790x330x545mm